

Termosoffiatore

HG5030K

1.600 W • 300 / 500 l/min • 350 / 500 °C

Termosoffiatore 1,600W 500° - 2 Vel

Termosoffiatore base da 1,600W dotato di impugnatura ergonomica per un uso impegnativo in diverse applicazioni, compresa la sverniciatura. Due impostazioni di calore e di flusso d'aria: velocità 1 - 350° per formatura, velocità 2 - 500° per termoretrazione, rimozione pitture, saldatura e operazioni di induritura. Fornisce fino a 500L/min a 500°C. Accessori in dotazione: 4 ugelli, valigetta.



SPECIFICHE TECNICHE

Max Potenza erogata	1600 W
Portata massima	300 / 500 L/min
Range temperatura	350 - 500 °
Interruttore di sicurezza termica	✓
Peso senza cavo (Procedura EPTA 01/2003)	0,56 kg
Dimensioni prodotto	233 x 80 x 208 mm
Cavo di alimentazione	2,0 m

Codice EAN 0088381857321

Collegamento alla pagina del prodotto - www.makita.it



PRODOTTI CORRELATI

ACCESSORI IN DOTAZIONE

PR00000028

Glass Protection Nozzle 45mm



PR00000029

Wide Slot Nozzle, 50 mm



PR00000030

Reflection Nozzle, 40 mm



PR00000031

Reduction Nozzle, 20 mm



ACCESSORI OPTIONAL

PR00000029

Wide Slot Nozzle, 50 mm



PR00000030

Reflection Nozzle, 40 mm



PR00000031

Reduction Nozzle, 20 mm



PR00000032

Overlap Welding Nozzle, 24 mm



PR00000033

Reflection Nozzle, 5 mm



PR00000034

Welding Nozzle, 65 mm



PR00000035

Pressure roller



PR00000036

Welding Rods, ABS, 5 x 230 mm, 10



PR00000037

Welding Rod, HDPE, 10 pcs



PR00000038

Welding Rod, PP, 10 pcs



PR00000039

Speed Welding Nozzle



PR00000041

Scraper Set



PR00000042

Contour Scraper

